



# COATINGS TECHNOLOGY (PTY) LTD

Re-Tek Power House  
Hv/Cnr Jenner & Lister Str/St  
Vanderbijlpark, 1911

Posbus / PO Box 1576  
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146  
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

0045

## PRODUCT DATA SHEET RETEK HEAVY DUTY FLOOR EPOXY

### Description

Retek Floor epoxy systems are designed to provide protection, easy to clean and maintain to new and existing concrete floors.

We offer a variety of colours, which comes in pre-measured kit form.

### Recommended uses

This is a low cost flooring system which can be applied over your existing concrete, ceramic or quarry tile, wood and metal. It can also be installed on vertical surfaces such as steps, walls.

- House floors
- Warehouse
- Bathroom
- Laboratories
- Garage
- Walk ways
- Workshops
- Locker and tea room
- Store room
- Food process areas

### Application

All surfaces should be cleaned from all loose debris, dust, oils, grease, animal fats etc.

- Mix part A separately, then add Part B and mix thoroughly
- Use Epoxy roller, brush only recommended for corners and touch-up.
- No Primer needed.

Exposure	Splash and Spillage	Fumes
Acids	Good	Very Good
Alkalise	Fair	Good
Solvents	Good	Very Good
Salt	Excellent	Excellent
Water	Excellent	Excellent
UV: Excellent		

**Coverage**

± 3m<sup>2</sup>/per kg at 250 microns dry film thickness.

**Drying Times**

24 Hours at ± 20°C.

**Shipping weight**

- Part A and B - 5kg
- Retek Thinners 30 – 5kg