

Re-Tek Power House
Hv/Cnr Jenner & Lister Str/St
Vanderbijlpark, 1911

Posbus / PO Box 1576
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

No. 128

High Build Floor Epoxy

Description

High Quality seamless, chemical resistant, non-slip hygienic Epoxy Floor System for Industrial, Commercial, Pharmaceutical, Automotive and Beverage Industries. Excellent adhesion to all most any thing.

Recommended uses

This is a cost effective flooring system which can be applied over your existing or new concrete, wood, metal, ceramic or quarry tiles.

- Ware Houses
- Workshops
- Industrial Plants
- Walk Ways
- Panel Beaters
- Filling Station Drive Way's
- Laboratories

Application

- All surfaces should be cleaned from all loose debris, dust, oils, grease, animal fats etc.
- Mix part A separately, then add Part B and mix thoroughly
- Use Epoxy roller, brush only recommended for corners and touch-up.

Coverage

250 microns - $\pm 3\text{m}^2$ /Per Kg.
500 – 1000 microns - $\pm 1.5\text{m}^2$ /Per Kg.

Drying Times

± 48 Hours at $\pm 20^\circ\text{C}$.