



RETEK COATINGS TECHNOLOGY (PTY) LTD

Re-Tek Power House
Hv/Cnr Jenner & Lister Str/St
Vanderbijlpark, 1911

Postbus / PO Box 1576
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

020

RETEK SUPER ACRYLIC EXTERIOR AND INTERIOR COATING

Super Acrylic is an durable and washable Interior and Exterior paint that is based on a superior quality acrylic emulsion. It is washable and can be used where heavy traffic might be encountered.

Super Acrylic Exhibits the following features:

- It's fully washable even after years of exposure.
- Resistant to rain and sun after years of exposure.
- It has superior hiding power.
- It is mould and water resistant.
- It contains no harmful agents.
- The product is manufactured from high quality acrylic emulsion that has high extensibility.
- Excellent adhesion.
- Water based, so cleaning of equipment is a feast.
- Only requires one or two coats on most surfaces and does not need any undercoat.
- Can easily be over coated.
- It comes in an existing range of colours.

Super Acrylic can be used on the following surfaces:

- Brick
- Cement Plaster walls
- Gypsum based plaster and gypsum board
- Wood and wood-based products
- Previously painted surfaces. (Pre-treatment might be required, depending on the surface)

All Weather exhibits the following features:

- Textured finish
- It is resistant to rain and sun even after years of exposure
- It is resistant to flaking when applied in the correct manner
- It can be washed with a soft bristle brush, using soft soap and water
- It comes in an existing range of colours

- It has superior hiding power
- It is mould and water resistant and will not blister if used correctly
- It contains no harmful agents
- It has an agreeable odour on application which will disappear in a short period of time
- It is manufactured from a high quality acrylic emulsion that has high extensibility
- Excellent adhesion
- Water based, so cleaning of equipment is a feast
- Only requires one or two coats on most surfaces and does not need any undercoat?
- Can easily be over coated

All Weather can be used on the following surfaces:

- Brick
- Cement plastered walls
- Gypsum based plaster and gypsum board
- Wood and wood-based products
- Previously painted surfaces (pre-treatment might be required, depending on the surface)

Application procedures

- Clean all surfaces from dust, oil or other contaminants
- Defects can be filled with an appropriate filler
- Super Acrylic can be applied by roller or brush
- Stir thoroughly before use
- Apply one or two coats of Super Acrylic, allowing a dry time of about two hours between coats.
- As this material is very easy to apply, care should be taken not to overspread
- After application, the equipment and any spillage can be cleaned with water and soap followed by thorough rinsing with clean water.
- On porous surfaces the first coat can be thinned with water (20%) or otherwise the surface can be wetted by means of fine water spray and the coating applied while still damp

Maintenance of All Weather painted surfaces

Surfaces that have been coated with Super Acrylic are very easy to maintain – Just wash with an ordinary household cleaner or soft soap by using a soft bristle brush and it will be resorted to its original pristine condition.

Product information

Super Acrylic is supplied in 1,5 and 20 litre containers
 A wide range of colours is available
 It has a spreading rate of 8-9 Mertes² per litre